



LEAK DETECTOR HFC 92 S

Leak detector designed for all new refrigerant gases
R22, R134a, R404, R407c, R410a - R600, R290 - NH3

Portable, batteries operating and reliable, the HFC 92 S
as essentially been designed for use on
worksites and intermittent applications.

Sensibility

From 1 to 30 gr/year
2 positions sensitivity.
Light array : 1, 2, 3, 5, 10.
Buzzer audible signal past light 3.

Warm up time

1mn about Automatic zeroing

Response time

1 second

Saturation Contamination Light

A progressive light indicate the local
contamination or the saturation of the
sensor.

Detection with suction

For effectiveness and good
localisation of the leak.

Interchangeable detection block

Long time of use.
Including sensor and pump.
Easy to handle with a spirally cable and a
fast connecting plug.
Interchangeable flexible sniffer pipe

Built in rechargeable batteries

4 hours autonomy on continuous operation.

Maintenance

Designed for an industrial purpose, the wearing parts (detection block, flexible pipe and spirally cable) can be easily replaced in a short time.



Performances controlled according
EN 14624 standard

Shockproof plastic cabinet

22 x 6,5 x 3 cm
Weight : 350 gr

Plastic carrying case

Delivered complete with charger and
Instructions for use

Optional parts :

Car lighter connexion plug for recharge
Test leak - value 5 gr/year R134a

SAPRE
maker

9, Ch. du Marbre Noir 13100 AIX-EN-PROVENCE
Tél. 04 42 21 90 48 Fax 04 42 21 90 65